

SAFETY DATA SHEET



Brushable Zinc Coating

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Brushable Zinc Coating
UFI : 4XM0-K0W4-V000-9N5P
Product code : 150010
Color : Silver.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Metal plating.-Paint.

1.3 Details of the supplier of the safety data sheet

WEICON GmbH & Co. KG
Königsberger Str. 255
48157 Münster
Germany
Phone: +49 251 93220
Fax: +49(0)251 / 9322 - 244
Internet: www.weicon.de

e-mail address of person responsible for this SDS : msds@weicon.de

1.4 Emergency telephone number

Telephone number : EMERGENCY CONTACT – UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel: ++44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Sens. 1, H317
STOT SE 3, H335
STOT SE 3, H336
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



SECTION 2: Hazards identification

Signal word	:	Warning
Hazard statements	:	<p>H226 - Flammable liquid and vapor. H317 - May cause an allergic skin reaction. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H410 - Very toxic to aquatic life with long lasting effects.</p>
<u>Precautionary statements</u>		
Prevention	:	<p>P280 - Wear protective gloves. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P261 - Avoid breathing vapor.</p>
Response	:	<p>P391 - Collect spillage. P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.</p>
Storage	:	<p>P405 - Store locked up. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.</p>
Disposal	:	P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	:	<p>Hydrocarbons, C9 aromatics Fatty acids, C14-18 and C16-18-unsatd., maleated maleic anhydride</p>
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Zinc powder zinc dust (stabilised)	REACH #: 01-2119467174-37 EC: 231-175-3 CAS: 7440-66-6 Index: 030-001-01-9	≥25 - ≤50	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1] [2]
Hydrocarbons, C9 aromatics	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: -	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1] [2]

SECTION 3: Composition/information on ingredients

xylylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	<10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
aluminium powder (stabilised)	REACH #: 01-2119529243-45 EC: 231-072-3 CAS: 7429-90-5 Index: 013-002-00-1	≤10	Flam. Sol. 1, H228 Water-react. 2, H261	[2]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: -	≤10	Asp. Tox. 1, H304 EUH066	[1] [2]
Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	REACH #: pre-registered EC: 269-662-8 CAS: 68308-64-5	<1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	[1]
Fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2120097630-54 EC: 288-306-2 CAS: 85711-46-2	<1	Skin Irrit. 2, H315 Skin Sens. 1, H317	[1]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E1	5000 tonne 100 tonne	50000 tonne 200 tonne

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Zinc powder zinc dust (stabilised)	DFG MAC-values list (Germany, 7/2019). TWA: 2 mg/m ³ 8 hours. Form: inhalable fraction PEAK: 4 mg/m ³ , 4 times per shift, 15 minutes. Form: inhalable fraction PEAK: 0.4 mg/m ³ , 4 times per shift, 15 minutes. Form: respirable fraction TWA: 0.1 mg/m ³ 8 hours. Form: respirable fraction
Hydrocarbons, C9 aromatics	TRGS 900 OEL (Germany).

SECTION 8: Exposure controls/personal protection

<p>xylene</p>	<p>AGW: 100 mg/m³</p> <p>TRGS 900 OEL (Germany, 10/2020). Absorbed through skin. TWA: 220 mg/m³ 8 hours. PEAK: 440 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. PEAK: 100 ppm 15 minutes.</p> <p>DFG MAC-values list (Germany, 8/2020). Absorbed through skin. TWA: 50 ppm 8 hours. PEAK: 100 ppm, 4 times per shift, 15 minutes. TWA: 220 mg/m³ 8 hours. PEAK: 440 mg/m³, 4 times per shift, 15 minutes.</p>
<p>aluminium powder (stabilised)</p>	<p>TRGS 900 OEL (Germany, 3/2020). TWA: 1.25 mg/m³ 8 hours. Form: alveolar fraction PEAK: 2.5 mg/m³ 15 minutes. Form: alveolar fraction PEAK: 20 mg/m³ 15 minutes. Form: inhalable fraction TWA: 10 mg/m³ 8 hours. Form: inhalable fraction</p> <p>DFG MAC-values list (Germany, 7/2019). TWA: 4 mg/m³ 8 hours. Form: inhalable dust TWA: 1.5 mg/m³ 8 hours. Form: respirable dust</p>
<p>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics</p>	<p>TRGS 900 OEL (Germany). AGW: 100 mg/m³</p>
<p>maleic anhydride</p>	<p>TRGS 900 OEL (Germany, 10/2020). Skin sensitizer. Inhalation sensitizer. TWA: 0.081 mg/m³ 8 hours. CEIL: 0.2025 mg/m³ TWA: 0.02 ppm 8 hours. CEIL: 0.05 ppm PEAK: 0.081 mg/m³ 15 minutes. PEAK: 0.02 ppm 15 minutes.</p> <p>DFG MAC-values list (Germany, 8/2020). Skin sensitizer. Inhalation sensitizer. TWA: 0.02 ppm 8 hours. CEIL: 0.05 ml/m³ TWA: 0.081 mg/m³ 8 hours. CEIL: 0.2 mg/m³ PEAK: 0.081 mg/m³, 4 times per shift, 15 minutes. PEAK: 0.02 ppm, 4 times per shift, 15 minutes.</p>

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects	
Zinc powder zinc dust (stabilised)	DNEL	Long term Oral	0.83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	2.5 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	5 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic	
xylene	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	14.8 mg/m ³	General population	Systemic	
	DNEL	Long term Inhalation	77 mg/m ³	Workers	Systemic	
	DNEL	Long term Dermal	108 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Inhalation	289 mg/m ³	Workers	Local	
	DNEL	Short term Inhalation	289 mg/m ³	Workers	Systemic	
	Fatty acids, C14-18 and C16-18-unsatd., maleated	DNEL	Long term Oral	1.67 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	1.67 mg/kg bw/day	General population	Systemic
		DNEL	Long term Dermal	3.33 mg/kg bw/day	Workers	Systemic
maleic anhydride	DNEL	Long term Inhalation	0.05 mg/m ³	General population	Systemic	
	DNEL	Long term Oral	0.06 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.08 mg/m ³	General population	Local	
	DNEL	Short term Oral	0.1 mg/kg bw/day	General population	Systemic	
	DNEL	Short term Dermal	0.1 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.1 mg/kg bw/day	General population	Systemic	
	DNEL	Long term	0.19 mg/m ³	Workers	Systemic	

SECTION 8: Exposure controls/personal protection

		Inhalation			
	DNEL	Short term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.32 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.8 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.8 mg/m ³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber ; 4 - 8 hours (breakthrough time): Viton®/butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Silver.
- Odor** : Aromatic. Benzene-like.
- Odor threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : 36°C (276.8°F)
- Flammability (solid, gas)** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
- Upper/lower flammability or explosive limits** : Lower: 0.6%
Upper: 7%
- Flash point** : Closed cup: 36°C (96.8°F)
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Kinematic (40°C): >21 mm²/s
- Solubility(ies)** : Insoluble in the following materials: cold water and hot water.
- Solubility in water** : Not available.
- Miscible with water** : No.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapor pressure** :

Ingredient name	Vapor Pressure at 20 °C			Vapor pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Xylene	6.7	0.89				
Hydrocarbons, C9 aromatics	1.5001	0.2				
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	0.37503	0.05				
Fatty acids, C14-18 and C16-18-unsatd., maleated	0.3	0.04		1.5	0.2	
maleic anhydride	0.25	0.033				

- Evaporation rate** : Not available.
- Relative density** : Not available.
- Density** : 1.15 g/cm³ [20°C (68°F)]
- Vapor density** : Not available.
- Explosive properties** : Not available.

Brushable Zinc Coating

SECTION 9: Physical and chemical properties

Oxidizing properties : Not available.

Particle characteristics

Median particle size : Not applicable.

Fire point : >200°C

SADT : Not applicable.

SAPT : Not applicable.

Flow time (ISO 2431) : 70 to 90 s (room temperature) [Jet diameter: 4 mm]

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidizing materials

10.6 Hazardous decomposition products : Highly reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.
Product may release hydrogen - avoid sources of ignition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<input checked="" type="checkbox"/> xylene	LD50 Oral	Rat	4300 mg/kg	-
maleic anhydride	LD50 Dermal	Rabbit	2620 mg/kg	-
	LD50 Oral	Rat	400 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Route	ATE value
<input checked="" type="checkbox"/> Dermal	12500 mg/kg
Inhalation (vapors)	125 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
<input checked="" type="checkbox"/> Zinc powder zinc dust (stabilised)	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-

SECTION 11: Toxicological information

maleic anhydride	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Eyes - Severe irritant	Rabbit	-	1 %	-

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9 aromatics	Category 3	-	Respiratory tract irritation
xylene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
maleic anhydride	Category 1	inhalation	respiratory system

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9 aromatics	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

SECTION 11: Toxicological information

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> Zinc powder zinc dust (stabilised)	Acute EC50 0.005 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 10000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute IC50 65 µg/l Marine water	Algae - Nitzschia closterium - Exponential growth phase	4 days
	Acute LC50 65 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 68 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 12.21 µg/l Marine water	Fish - Periophthalmus waltoni - Adult	96 hours
	Chronic EC10 27.3 µg/l Fresh water	Algae - Pseudokirchneriella	72 hours

SECTION 12: Ecological information

xylene	Chronic EC10 59.2 µg/l Fresh water	subcapitata - Exponential growth phase	
	Chronic NOEC 9 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 178 µg/l Marine water	Aquatic plants - Ceratophyllum demersum	3 days
	Chronic NOEC 2.6 µg/l Fresh water	Crustaceans - Palaemon elegans	21 days
	Acute EC50 90 mg/l Fresh water	Fish - Cyprinus carpio	4 weeks
	Acute LC50 13400 µg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
maleic anhydride	Acute LC50 230 ppm Fresh water	Fish - Pimephales promelas	96 hours
		Fish - Gambusia affinis - Adult	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 to 25.9	low
maleic anhydride	-2.78	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Brushable Zinc Coating

SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances






Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
15 01 04	metallic packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT mixture	PAINT	Paint
14.3 Transport hazard class(es)	3  	3  	3 
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes. Zinc powder - zinc dust (stabilized), Hydrocarbons, C9 aromatics	Yes. Zinc powder - zinc dust (stabilized), Hydrocarbons, C9 aromatics	Yes. The environmentally hazardous substance mark is not required.

Additional information

- ADR/RID** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Hazard identification number 30
Limited quantity 5 L
Special provisions 163, 650, 367
Tunnel code (D/E)
ADR Classification Code: F1
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Emergency schedules F-E, _S-E_
Special provisions 163, 223, 367, 955
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
Quantity limitation Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344.
Special provisions A3, A72, A192

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Restrictions on Manufacture, Marketing and Use

Product name	CAS #	%	Restriction
Hydrocarbons, C9, aromatics	-	20 - 30	3
xylene	1330-20-7	1 - 10	3
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	1 - 10	3

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

VOC content : 38.76 %

VOC (g/L) : 445.73

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Brushable Zinc Coating

SECTION 15: Regulatory information

Category

P5c
E1

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
Zinc powder zinc dust (stabilised)	DFG MAC-values list	Zinc and its inorganic compounds (inhalable fraction) / (respirable fraction)	Listed	-
xylene	DFG MAC-values list	Xylene (all isomers)	Listed	-
aluminium powder (stabilised)	DFG MAC-values list	Aluminium, Aluminium oxide and Aluminium hydroxide, containing dusts (inhalable fraction) / (respirable fraction)	Listed	-
maleic anhydride	DFG MAC-values list	Maleic anhydride	Listed	-

Storage class (TRGS 510) : 3

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category	Reference number
P5c	1.2.5.3
E1	1.3.1

Hazard class for water : 3

Technical instruction on air quality control : A-Luft Class III - Number 5.2.2: 25-50%
TA-Luft Number 5.2.5: 22.1-51%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: Not determined.
Canada	: <input checked="" type="checkbox"/> At least one component is not listed in DSL but all such components are listed in NDSL.
China	: <input checked="" type="checkbox"/> All components are listed or exempted.
Europe	: All components are listed or exempted.
Japan	: Not determined.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.

Brushable Zinc Coating

SECTION 15: Regulatory information

Turkey	: Not determined.
United States	: <input checked="" type="checkbox"/> All components are active or exempted.
Viet Nam	: Not determined.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative
-----------------------------------	--

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
<input checked="" type="checkbox"/> Flam. Liq. 3, H226 Skin Sens. 1, H317 STOT SE 3, H335 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

<input checked="" type="checkbox"/> H226 H228 H261 H302 H304 H312 H314 H315 H317 H318 H319 H332 H334 H335 H336 H372 H400 H410 H411 H412 EUH066 EUH071	Flammable liquid and vapor. Flammable solid. In contact with water releases flammable gas. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Corrosive to the respiratory tract.
--	---

Full text of classifications [CLP/GHS]

SECTION 16: Other information

<p> <input checked="" type="checkbox"/> Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 3 Flam. Sol. 1 Resp. Sens. 1 Skin Corr. 1B Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT RE 1 STOT SE 3 Water-react. 2 </p>	<p> ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 FLAMMABLE SOLIDS - Category 1 RESPIRATORY SENSITIZATION - Category 1 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3 SUBSTANCES AND MIXTURES, WHICH IN CONTACT WITH WATER, EMIT FLAMMABLE GASES - Category 2 </p>
--	--

Date of printing : 10.08.2021

Date of issue/ Date of revision : 10.08.2021

Date of previous issue : 02.06.2020

Version : 3

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.