



product description:

designed for distribution system with voltage 400 V and with maximum current 16 A
 intended for devices of Classic and Swing - ABB series
 suitable for installation doublesocket
 on the sides of the box are marked inlets for the trunkings
 to install on materials with fire classes E or F, use insulating pad

material: PVC

color: white / imitation pink birch / imitation dark oak / light brown

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-D

weight: 54 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

LK 80X28 2ZK_HB - 10 pcs of boxes including device screws packed in foil; 80 pcs of boxes in carton; color - white

LK 80X28 2ZK_I1 - 10 pcs of boxes including device screws packed in foil; 80 pcs of boxes in carton; color - imitation pink birch

LK 80X28 2ZK_I2 - 10 pcs of boxes including device screws packed in foil; 80 pcs of boxes in carton; color - imitation dark oak

LK 80X28 2ZK_SD - 10 pcs of boxes including device screws packed in foil; 80 pcs of boxes in carton; color - light brown

accessories:

screwless terminal plates TYP015, TYP016, TYP017, TYP018

thermo-insulating pad PI 80 2ZK

