



product description: intended for installation to the distribution of low voltage  
 standard shape  
 designed for wall or ceiling mounting  
 double lock on lid increasing the trunking's rigidity and ensuring stronger cover fixation  
 possibility to install in places with risk of flammable gases and vapor – danger zone 2  
 possibility to install in places with explosive risk of dust – danger zone 22  
 the \_P2 configuration - adhesive tape on the back side for easier fixing of the trunking before final installation to the substrate material

material: PVC - Pb-free  
 self-snuffing: yes, within 30 s  
 temperature resistance: -5 - +60 °C  
 flaming loop test: 850 °C  
 impact strength: 0,5 J  
 protection types: IP40  
 fire class for underlying material: A1-F  
 inside area: 190 mm<sup>2</sup>  
 distance base perforation: 200 ±20 mm, Ø 4,5 mm  
 length tolerance: ±10 mm  
 weight: 0,11 kg/m  
 mechanical protection according to EN 50102: IK06  
 meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07  
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

trunkings are not a breeding ground for bacteria, tested in SZÚ according to ČSN EN ISO 846:2019

List of bacteria that have been tested:  
 ESCHERICHIA COLI, STAPHYLOCOCCUS AUREUS, KLEBSIEL/A PNEUMONIAE, PSEUDOMONAS AERUGINOSA,  
 ENTEROCOCCUS FAECALIS, BACILLUS SUBTILIS, SALMONELLA ENTERICA, LEGIONELLA PNEUMOPHILA, CANDIDA  
 ALBICANS

item number	length	color	package	package - description	note
<b>LHD 17X17_HC</b>	2 m	white RAL 9003	176 m	foil	without protective foil
<b>LHD 17X17_HD</b>	2 m	white RAL 9003	70 m	carton	with protective foil
<b>LHD 17X17_P2</b>	2 m	white RAL 9003	70 m	carton	with self-adhesive tape
<b>8671_HB</b>		white RAL 9003	10 / 100 / 1200 pcs	foil / foil / carton	end
<b>8672_HB</b>		white RAL 9003	10 / 100 / 1400 pcs	foil / foil / carton	connecting
<b>8673_HB</b>		white RAL 9003	10 / 1440 pcs	foil / carton	bending
<b>8674_HB</b>		white RAL 9003	10 / 900 pcs	foil / carton	branching
<b>8675_HB</b>		white RAL 9003	10 / 100 / 1000 pcs	foil / foil / carton	inner corner
<b>8676_HB</b>		white RAL 9003	10 / 1360 pcs	foil / carton	outer corner

recycling symbols:



PVC trunkings, PVC covers



Protective film, adhesive tape, packaging film for trunkings, bags, and packaging film for covers



cardboard

usage of inner trunking cross-section (60%):

orientation cable diameter (mm)	6	7	8	8,5	9
number of inserted cables	2	1	1	1	1

Risks Associated with Product Use:

- during installation, use appropriate protective work equipment and follow safety guidelines
- use the product only for the purposes intended by the manufacturer
- use the product in an environment that complies with the manufacturer's instructions
- do not use the product if it is damaged
- follow the manufacturer's recommendations and do not exceed the number of inserted cables or the product's load capacity
- after installation, check the correctness of the mounting of trunkings and covers according to the manufacturer's recommendations